## (19) World Intellectual Property Organization International Bureau



## 

(43) International Publication Date 24 December 2003 (24.12.2003)

## (10) International Publication Number WO 2003/106993 A3

(51) International Patent Classification7: G01N 29/10, G01B 17/00

(21) International Application Number:

PCT/US2003/019133

(22) International Filing Date: 17 June 2003 (17.06.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/389,394

17 June 2002 (17.06.2002)


(71) Applicant (for all designated States except US): SWAGELOK COMPANY [US/US]; 2950 Solon Road, Solon, OH 44139 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): ALES, Richard, A. [US/US]; 6455 Southgrove Road, Mentor, OH 44060 (US). Leicestershire LE14 2QG (GB). RUBINSKI, Jeffrey, M. [US/US]; 2214 Buena Vista Drive, Wickliffe, OH 44092 (US). SEYMOUR, Michael, Douglas [GB/GB]; Pear Tree Lodge, 2A Scrimshire Lane, Cotgrave, Nottinghamshire NG12 3JD (GB). WILLIAMS, Peter, C. [US/US]; 3495 Edison Road, Cleveland Heights, OH 44121 (US). YANG, Wenxian [GB/GB]; 59A Montpelier Road, Dunkirk, Nottinghamshire NG7 2JY (GB).

(74) Agent: MCKNIGHT, Douglas, B.; Calfee, Halter & Griswold LLP, 800 Superior Avenue, Cleveland, OH 44114 (US).

- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.



Application of the input energy collected at different radial positions about a first axial location is used with wavelet based correlation techniques to better analyze the reflected energy signals. Quality of the abutment between the conduit end and a surface associated with the coupling may also be determined as a separate or combined feature of the axial position determination.